



<p>Hardener 133 Hardener for epoxy resin Contains: Benzyalkohol <25%; Isophoronediamine <25%; 3-Aminopropyltrimethoxysilane<5%; Polyoxyalkyleamines >50% Producer / Importer : GRM Systems s.r.o. Slatinky 158, 78342 Česká r. Phone: 585 431 734 e-mail:info@grm-systems.cz Seller : GALASPORT,s.r.o. Tedražice 82, 342 01 Hrádek, ČR IČO 25246283 tel.+420 602428895</p>	 C Corrosive  Xn Harmful	<p>R 20</p>	
		<p>R 21 R 22</p>	<p>Harmful by inhalation, in contact with skin and if swallowed.</p>
		<p>R 34</p>	<p>Causes burns.</p>
		<p>R 43</p>	<p>May cause sensitisation by skin contact.</p>
		<p>S 2</p>	<p>Keep out of the reach of children.</p>
		<p>Avoid contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection.</p>	
		<p>First aid :</p>	
		<p><u>After contact with skin</u>, take off immediately all contaminated clothing and wash immediately with plenty of water and soap.</p>	
		<p><u>In case of accident by inhalation</u>: remove casualty to fresh air and keep at rest. <u>In case of contact with eyes</u>, rinse immediately with plenty of water and seek medical advice. <u>If swallowed</u>, rinse mouth with water (only if the person is conscious), seek medical advice. and show this container or label.</p>	
<p>Mix with the hardener 133 in weight ratio : 100 parts of the resin : 35 parts of the hardener</p>			
<p>Pot life : approx. 20min.</p>			
<p>Curing : At room temperature.</p>			
<p>Store in a dark room, well closed .</p>			
<p>Expiration date : /202</p>			
<p>Net weight: 65g</p>			